



Paramount Minerals and Chemicals Limited

(An ISO 9001:2008, ISO 14001:2004 & OHSAS18001:2007 Certified Company)

DOLOSOLZ WG

*Acrylic Acid Homopolymer
Scale Inhibitor*

	DOLOSOLZ WG
Grade	Na Salt
Form	Clear to slightly yellowish solution
Percentage solids	43%
Viscosity, cps at 25 deg C	150-250
Density at 25 deg C	1.30-1.36 g/cm cube
pH as is at 25-30 deg C.	6.50-7.50
Average molecular weight	2,000
Storage stability	24 months from manufacture in unopened drums safely stored containers
Recommended for Use	In Industrial Water Treatment <ul style="list-style-type: none">- Inhibits scale formation in open recirculating cooling circuits (particularly CaCO₃ scale)- Dispersant for boiler sludge control In Oil field water treatment for scale prevention in formation and production equipment

Dolosolz WG is a general purpose scale inhibitor which is effective in preventing precipitation and deposition of barium sulfate, calcium oxalate, calcium sulfate, calcium carbonate and other low solubility salts through threshold effect by solubility enhancement.

With the process of crystal modification Dolosolz WG deforms inorganic salt crystals which then do not adhere well to surfaces and can be easily removed during cleaning.

Dolosolz WG through its dispersing characteristic prevents agglomeration and depositing on surfaces of precipitated crystals or other inorganic particles.

Benefits:

- Excellent Hypochlorite stability
- Effective at wide pH range, water hardness and temperature conditions
- Excellent dispersant characteristic
- Free from phosphorus and therefore suitable for regions requiring phosphorus free discharge waters

Storage

It is recommended to store Dolosolz WG at temperature above freezing. Freezing or long term cold storage may cause separation, this does not impair product performance if the entire contents are heated and well mixed.